



### Flexibility and Scalability

- Cost effective access solution
- Off-line installation, no wires required
- Non-volatile memory and audit trail
- Suitable for outdoors and extreme weather conditions with weather kit
- Fits all types of doors with a 5" stile or larger, new construction and retrofit
- Supports MIFARE Classic®, MIFARE Plus®, MIFARE Ultralight®, and MIFARE Ultralight C cards
- Reading technology: contactless RFID (ISO14443A, NFC)
- DirectKey-ready: Optional on-board DirectKey module provides secure wireless communication of credentials from a user's smartphone to a locking device via Bluetooth® Smart communications

### Components:

- Electronic lock
- Panic bar
- Interface kit
- Face plate
- Mounting screws

### Options:

- K2 Commercial Hardware Series QED100
- Von Duprin® 98/99 Series Rim Panic Interface
- TownSteel 9700 Series Hardware

### Specifications:

- Designed to ANSI Grade 1 specifications
- Temperature tolerances ranges:  
Alkaline batteries: 0°F / 130°F (-18°C / 55°C)  
For non-fire rated doors only  
Lithium batteries: -40°F / 167°F (-40°C / 75°C)
- ADA compliant
- Humidity tolerance: up to 95% without condensation
- Power supply: 4 standard alkaline 1.5 volt batteries

### Part Numbers:

- K2 Series QED 100 Rim Panic Interface Kit  
KHA3T-RIM-626  
Also available in other finishes
- Von Duprin® 98/99 Series Rim Panic Interface  
KHA3T-RPI1-626  
Also available in other finishes
- TownSteel 9700 Series Rim Panic Interface  
KHA3T-RPTS1-626  
Also available in other finishes

[onity.com](http://onity.com)  
800-424-1433